

VanWeigh



Overload Protection Load Optimisation

Optimised for LCV

"A few years ago I was in breach of weight regulations sitting behind my office desk. Whilst collecting castings from a foundry, our driver accepted an additional pallet. Stopped, weighed and subsequently prosecuted, the driver and I found ourselves pleading guilty at Burnley Magistrates Court...never again! We have recently installed VanWeigh systems to all our vehicles."

Glyn Brown,
Managing Director, Archerdale Limited

Axle Load Monitoring

The VanWeigh® axle overload monitoring system is specifically designed for two axled vehicles with standard coil or leaf spring suspension. Each axle is monitored with a patented solid-state sensor which monitors the load applied to each axle. The information is displayed to the driver on the twin channel digital indicator and an audible alarm sounds if the total vehicle or axle weight maximum is infringed.



Axle Sensor

The driver has a choice of three screens:

Screen 1: the standard dial screen view.

Screen 2: a graphical van display with the actual weight in kgs and the percent of payload vs load capacity.

Screen 3: an actual weight over each axle plus the GVW in kgs and the percent of payload vs load capacity.

The driver will be alerted to three conditions:

Safe: indicates loads up to 90% either front or rear axle and total load.

Warning: indicates loads between 90% and 100%.

Overload: alerts the driver to an axle or vehicle infringement above 100% load.

Durable

VanWeigh has no moving parts and is not susceptible to wear or slipping out of calibration because of stretched springs, which are common in other axle overload monitoring systems.

VanWeigh® Digital
Touch Screen Indicator



Safe Indication



Rear Axle Overload
Warning



Gross Overload
Warning



Each Axle Displayed
as a Percentage

Airedale House | Canal Road | Bradford BD2 1AG
Ph: +44 (0)1274 771177 | Fax: +44 (0)1274 781178
E-mail: obw.eur@vpgsensors.com

vpgonboard.com

VPG
ONBOARD
WEIGHING

Overload Protection – Load Optimisation

Optimised for LCV

Features and Benefits

- Better than $\pm 2.5\%$ (90%-100% of GVW)
- Colour touch screen
- Simple to operate
- No driver input required
- Axle overload warnings
- Gross overload warnings
- Balanced load distribution
- Maximise payload capacity
- Operating tolerance of vehicle (braking)
- Possible reduced fuel consumption
- Reduce vehicle wear and tear
- Protect your licence
- Avoid fines
- Avoid overload endorsements



Telematics Output

VanWeigh® includes an output from the indicator capable of connecting with tracking systems, allowing communications between the two systems which is reliable and easy to achieve.

An optional cable is supplied with the VanWeigh system which allows telematics systems to capture the weight information and alarm triggers.


System Specification

Accuracy:	Better than $\pm 2.5\%$ (90%-100% of GVW)
Safe Weight Setting:	Up to 90%
Warning:	90%–100%
Overload Setting:	Over 100%
Power Supply:	12/24 Volt
Operating Current:	<400 mA
Standby Current:	<5 mA
Screen Resolution:	480 x 272 pixels

Environmental Tests

Electrical Tests Passed for E and CE Marking Requirements

Environmental Performance Exceeds SAE J1455



DISCLAIMER: ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE. Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product. The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein. VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.** Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com. No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG. The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications. Product names and markings noted herein may be trademarks of their respective owners.